



Good bonds last.

## SAFETY DATA SHEET

### Section 1. Identification of the material and the supplier

Product: Sabre Grip S20 500ml Aerosol Spray Adhesive  
Product Use: Adhesive.  
Restriction of Use: Refer to Section 15

**New Zealand Supplier:** Sabre Adhesives Ltd  
Address: 42 Cambridge Street South  
Levin, 5510, New Zealand  
Telephone: +64 (0)6 366 0007  
**Emergency No:** **0800 764 766 (National Poison Centre)**

**Australian Supplier:** Sabre Adhesives Ltd  
Address: Level 6, 10 Herb Elliot Avenue, Sydney NSW, 2127  
Telephone No: +61 2 9098 8244  
**Emergency No:** **13 11 26 (National Poison Line)**

Date SDS Issued: 3 May 2023 v2

### Section 2. Hazards Identification

#### Australia:

Classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia

#### New Zealand:

This substance is hazardous according to the EPA Hazardous Substances (Classification) Notice 2020

**NZ - EPA Approval Code:** Aerosols (Flammable, Carcinogenic) - HSR002517

#### Pictograms



**SIGNAL WORD: DANGER**

GHS Category	Hazard Code	Hazard Statement
Aerosol Cat. 1	H222	Extremely flammable aerosol.
	H229	Pressurised container: May burst if heated.
Acute oral toxicity Cat. 4	H302	Harmful if swallowed.
Skin irritation Cat. 2	H315	Causes skin irritation.
Eye irritation Cat. 2	H319	Causes serious eye irritation.
Carcinogenicity Cat. 2	H351	Suspected of causing cancer.

Product Name: Sabre Grip S20 500ml Aerosol  
Date of SDS: 3 May 2023

SDS Prepared by: Technical Compliance Consultants (NZ) Ltd  
Tel: +64 9 475 5240 WWW.techcomp.co.nz

Specific target organ toxicity - repeated exposure Cat. 2	H373	May cause damage to organs through prolonged or repeated exposure.
---	------	--

**Prevention Code    Prevention Statement**

P102	Keep out of reach of children.
P103	Read carefully and follow all instructions.
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P260	Do not breathe fumes, gas, mist, vapours or spray.
P264	Wash hands thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P280	Wear protective clothing as detailed in Section 8.
P281	Use personal protective equipment as required.

**Response Code    Response Statement**

P101	If medical advice is needed, have product container or label at hand.
P314	Get medical advice/attention if you feel unwell.
P330	Rinse mouth.
P362	Take off contaminated clothing and wash it before reuse.
P301 + P312	IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P305 + P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313	IF exposed or concerned: Get medical advice/ attention.
P332 + P313	If skin irritation occurs: Get medical advice/ attention.
P337 + P313	If eye irritation persists: Get medical advice/attention.

**Storage Code    Storage Statement**

P403	Store in a well-ventilated place.
P405	Store locked up.

**Disposal Code    Disposal Statement**

P501	Dispose of according to the local authorities
------	---

**Section 3.    Composition of hazardous Ingredients**

Ingredients	Wt%	CAS NUMBER.
Methylene chloride	40-60	75-09-2
LPG (liquefied petroleum gas)	20-40	68476-85-7

**Section 4.    First Aid Measures**

Routes of Exposure:

If in Eyes                      Rinse cautiously with water for several minutes. Transport to hospital or doctor without delay. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

If on Skin                      Take off contaminated clothing and wash it before Wash with plenty of soap and water or recognised skin cleansing agent. DO NOT use solvents.

Continue to rinse for at least 15 minutes. If adhesive bonding occurs, do not force skin apart. If skin irritation or rash occurs: Get medical advice/attention.

**If Swallowed** Rinse mouth thoroughly with water. Give plenty of water to drink. Stop if the affected person feels sick as vomiting may be dangerous. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. Call a POISON CENTER or doctor/physician if you feel unwell.

**If Inhaled** Remove person to fresh air. Remove contaminated clothing and loosen remaining clothing. Allow person to assume most comfortable position and keep warm. Keep at rest until fully recovered. Get medical advice if breathing becomes difficult.

**Most important symptoms and effects, both acute and delayed**

**Symptoms:** Refer to Section 11 for all symptoms:

**Ingestion:** May cause stomach pain or vomiting. May cause drowsiness or dizziness. Prolonged or repeated exposure may cause the following adverse effects: Suspected of causing cancer.

**Inhalation:** A single exposure may cause the following adverse effects: Headache. Nausea, vomiting. Central nervous system depression. Drowsiness, dizziness, disorientation, vertigo. Narcotic effect. During application and drying, solvent vapours will be emitted. Vapours in high concentrations are narcotic. Prolonged or repeated exposure may cause the following adverse effects: Suspected of causing cancer.

**Skin:** Redness. Irritating to skin. Bonds skin and eyes in seconds. Prolonged or repeated exposure may cause the following adverse effects: Suspected of causing cancer.

**Eye:** Irritating to eyes. Bonds skin and eyes in seconds.

**Chronic:** Suspected of causing cancer.

**Notes to Doctor:** Treat symptomatically.

**Section 5. Fire Fighting Measures**

<b>Hazard Type</b>	Flammable Aerosol
<b>Hazards from products</b>	Fire may produce irritating, poisonous or corrosive gases. Runoff may create fire or explosion hazard. May decompose explosively when heated or involved in fire. Contact with gas may cause burns, severe injury and/ or frostbite. Combustion products include: carbon monoxide (CO) carbon dioxide (CO2) hydrogen chloride phosgene metal oxides other pyrolysis products typical of burning organic material.
<b>Suitable Extinguishing media</b>	SMALL FIRE: Water spray, dry chemical or CO2 LARGE FIRE: Water spray or fog.
<b>Precautions for firefighters and special protective clothing</b>	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to Australia/New Zealand Standards AS/NZS 4967 (for clothing) AS/NZS 1801 (for helmets), AS/NZS 4821 (for protective boots), AS/NZS 1801 (for protective gloves) will provide a basic level of protection for

	chemical incidents. If safe, switch off electrical equipment until vapour fire hazard removed. Use water delivered as a fine spray to control fire and cool adjacent area. DO NOT approach cylinders suspected to be hot. Cool fire-exposed cylinders with water spray from a protected location. If safe to do so, remove containers from path of fire.
<b>HAZCHEM CODE</b>	<b>2WE</b>

## **Section 6. Accidental Release Measures**

Keep unnecessary and unprotected personnel away from the spillage. Stop leak only if safe to do so. Wear protective clothing as described in Section 8 of this safety data sheet. Remove all ignition sources. Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes.

Prevent, by any means available, spillage from entering drains or water course.

Eliminate all ignition sources if safe to do so. No smoking, sparks, flames or other sources of ignition near spillage. Increase ventilation.  
Stop leak if safe to do so. Water spray or fog may be used to disperse / absorb vapour. Contain or absorb spill with sand, earth or vermiculite.  
Collect recoverable product into labelled containers for recycling. Collect solid residues and seal in labelled drums for disposal. Wash area and prevent runoff into drains.  
Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

## **Section 7. Handling and Storage**

### **Handling:**

- Read carefully and follow all instructions.
- Obtain special instructions before use.
- Do not handle until all safety precautions have been read and understood.
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- Do not spray on an open flame or other ignition source.
- Do not pierce or burn, even after use.
- Do not breathe fumes, gas, mist, vapours or spray.
- Wash hands thoroughly after handling.
- Do not eat, drink or smoke when using this product.
- Wear protective clothing as detailed in Section 8.
- Use personal protective equipment as required.
- DO NOT incinerate or puncture aerosol cans.
- Avoid physical damage to containers.

### **Storage:**

- Store away from incompatible materials listed in Section 10.
- Store locked up and out of reach of children.
- Store in a well-ventilated place.
- Keep away from oxidising materials, heat and flames.
- Keep only in the original container.
- Keep container tightly closed and in a well-ventilated place.
- Keep containers upright.
- Protect containers from damage.
- Protect from sunlight.
- Do not store near heat sources or expose to high temperatures.

## **Section 8 Exposure Controls / Personal Protection**

Product Name: Sabre Grip S20 500ml Aerosol  
Date of SDS: 3 May 2023

SDS Prepared by: Technical Compliance Consultants (NZ) Ltd  
Tel: +64 9 475 5240 WWW.techcomp.co.nz

**Exposure Limit Values:  
WORKPLACE EXPOSURE STANDARDS (provided for guidance only)**

Substance		TWA		STEL	
		ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>
Methylene chloride	[75-09-2]	50	174	-	-
LPG (Liquefied petroleum gas)	[68476-85-7]	1000	1800	-	-

Workplace Exposure Standard – Time Weighted Average (WES-TWA). The time-weighted average exposure standard designed to protect the worker from the effects of long-term exposure. Workplace Exposure Standard – Short-Term Exposure Limit (WESSTEL). The 15-minute average exposure standard. Applies to any 15- Minute period in the working day and is designed to protect the worker against adverse effects of irritation, chronic or irreversible tissue change, or narcosis that may increase the likelihood of accidents. The WES-STEL is not an alternative to the WES-TWA; both the short-term and time-weighted average exposures apply. Workplace Exposure Standards and Biological Exposure Indices APRIL 2022 13<sup>TH</sup> EDITION.

**Engineering Controls**

Provide adequate ventilation. Personal, workplace environment or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Use process enclosures, local exhaust ventilation or other engineering controls as the primary means to minimise worker exposure. Personal protective equipment should only be used if worker exposure cannot be controlled adequately by the engineering control measures. Ensure control measures are regularly inspected and maintained. Ensure the ventilation system is regularly maintained and tested. As this product contains ingredients with exposure limits, process enclosures, local exhaust ventilation or other engineering controls should be used to keep worker exposure below any statutory or recommended limits, if use generates fumes, gas, vapour or mist.

**Personal Protection Equipment**



<b>Eyes</b>	Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Personal protective equipment for eye and face protection should comply with Australia/New Zealand Standard AS/NZS 1337. Wear tight-fitting, chemical splash goggles or face shield.
<b>Hands</b>	Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. To protect hands from chemicals, gloves should comply with Australia/New Zealand Standard AS/NZS 2161. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Frequent changes are recommended.
<b>Skin</b>	Wear appropriate footwear and additional protective clothing.
<b>Respiratory</b>	Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Ensure all respiratory protective equipment is suitable for its intended use and complies with Australia/New Zealand Standard AS/NZS 1716. Check that the respirator fits tightly and the filter is changed regularly. Gas and combination filter cartridges should comply with Australia/New Zealand Standard AS/NZS 1716. Full face mask respirators with replaceable filter cartridges should comply with Australia/New Zealand Standard AS/NZS 1716. Half mask and quarter mask respirators with replaceable filter cartridges should comply with Australia/New Zealand Standard AS/NZS 1716.

**Section 9 Physical and Chemical Properties**

<b>Appearance</b>	Coloured Liquified Gas (Aerosol)
<b>Odour</b>	Not available
<b>Odour Threshold</b>	Not applicable
<b>pH</b>	Not applicable
<b>Boiling Point</b>	40°C
<b>Melting Point</b>	-97°C
<b>Freezing Point</b>	Not applicable
<b>Flash Point</b>	-104°C
<b>Flammability</b>	Highly Flammable
<b>Upper and Lower Explosive Limits</b>	Not available
<b>Vapour Pressure</b>	46.86 kPa
<b>Vapour Density (air=1)</b>	2.93
<b>Relative Density</b>	0.837
<b>Solubility in water</b>	Immiscible
<b>Partition Coefficient:</b>	Not applicable
<b>Auto-ignition Temperature</b>	Not available
<b>Solubility Value (g/100g H<sub>2</sub>O°C)</b>	Not available
<b>VOC density @ 20°C</b>	425.71 g/L
<b>Particle Characteristics</b>	Not applicable
<b>Evaporation Rate</b>	Not available

**Section 10. Stability and Reactivity**

<b>Stability of Substance</b>	Stable at normal ambient temperatures and when used as recommended. Stable at normal ambient temperatures and when used as recommended.
<b>Conditions to Avoid</b>	Avoid exposing containers to high temperatures or direct sunlight. Containers can burst violently or explode when heated, due to excessive pressure build-up.
<b>Incompatible Materials</b>	No specific material or group of materials is likely to react with the product to produce a hazardous situation. Store away from oxidizing and combustible materials.
<b>Hazardous Decomposition Products</b>	Refer to Section 5.

**Section 11 Toxicological Information****Acute Effects:**

<b>Swallowed</b>	Harmful if swallowed.
<b>Dermal</b>	Not applicable.
<b>Inhalation</b>	Not classified. The material is not thought to produce respiratory irritation (as classified). Nevertheless inhalation of the material, especially for prolonged periods, may produce respiratory discomfort and occasionally, distress. Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by sleepiness, reduced alertness, loss of reflexes, lack of co-ordination, and vertigo. Inhalation hazard is increased at higher temperatures. Inhalation of high concentrations of gas/vapour causes lung irritation with coughing and nausea, central nervous depression

	with headache and dizziness, slowing of reflexes, fatigue and inco-ordination.
<b>Eye</b>	Causes severe irritation to eyes. Moderate inflammation may be expected with redness; conjunctivitis may occur with prolonged exposure
<b>Skin</b>	Causes skin irritation. The material may accentuate any pre-existing dermatitis condition. Open cuts, abraded or irritated skin should not be exposed to this material. Entry into the blood-stream through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected. Vapourising liquid causes rapid cooling and contact may cause cold burns, frostbite, even through normal gloves. Frozen skin tissues are painless and appear waxy and yellow. Signs and symptoms of frost-bite may include "pins and needles", paleness followed by numbness, a hardening and stiffening of the skin, a progression of colour changes in the affected area, (first white, then mottled and blue and eventually black; on recovery, red, hot, painful and blistered). Skin contact with the material may damage the health of the individual; systemic effects may result following absorption. The material may cause severe inflammation of the skin either following direct contact or after a delay of some time. Repeated exposure can cause contact dermatitis which is characterised by redness, swelling and blistering.

#### Chronic Effects:

<b>Carcinogenicity</b>	Suspected of causing cancer.
<b>Reproductive Toxicity</b>	Not applicable.
<b>Germ Cell Mutagenicity</b>	Not applicable.
<b>Aspiration</b>	Not applicable.
<b>STOT/SE</b>	Not applicable.
<b>STOT/RE</b>	Causes damage to organs through prolonged or repeated exposure.

#### Individual component information:

##### Acute Toxicity:

Chemical Name	Oral – LD50	Dermal – LD50	Inhalation – LC50
Methylene chloride	1600 mg/kg (rat)	>2000mg/kg (rat)	76 mg/L/4hr (rat)
LPG (liquefied petroleum gas)	-	-	658 mg/L/4hr (rat)

#### METHYLENE CHLORIDE:

Inhalation (human) TCLo: 500 ppm/ 1 y - I Eye(rabbit): 10 mg - mild

The material may produce moderate eye irritation leading to inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

The material may cause severe skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin. Repeated exposures may produce severe ulceration.

WARNING: This substance has been classified by the IARC as Group 2A: Probably Carcinogenic to Humans.

#### Section 12. Ecotoxicological Information

This product is not hazardous to the environment.

Product Name: Sabre Grip S20 500ml Aerosol  
Date of SDS: 3 May 2023

SDS Prepared by: Technical Compliance Consultants (NZ) Ltd  
Tel: +64 9 475 5240 WWW.techcomp.co.nz

<b>Persistence and degradability</b>	No data available on product Methylene Chloride: <b>Persistence: Water/Soil</b> <b>Air</b> LOW(half-life=56 days) HIGH(half-life = 191 days) Water: LOW LOW
<b>Bioaccumulative</b>	No data available on product Methylene Chloride: LOW (BCF=40)
<b>Mobility in soil</b>	No data available on product Methylene Chloride: LOW (KOC=23.74)
<b>Other adverse effects</b>	No data available

**Individual component information:**

**Methylene chloride:**

Endpoint	Species	Duration	Value LC50/EC50
BCF	Fish	1008 hr	2-5.4
EC50(ECx)	Algae or other aquatic plants	96 hr	0.98 mg/L
EC50	Algae or other aquatic plants	72 hr	202-286 mg/L
EC50	Crustacean	48 hr	150-218 mg/l
LC50	Fish	96 hr	2-3.3 mg/L
EC50	Algae or other aquatic plants	96 hr	0.98 mg/l

**LPG (liquefied petroleum gas):**

Endpoint	Species	Duration	Value LC50/EC50
EC50(ECx)	Algae or other aquatic plants	96 hr	7.71 mg/L
LC50	Fish	96 hr	24.11 mg/L
EC50	Algae or other aquatic plants	96 hr	7.71 mg/L

**Section 13. Disposal Considerations**

**Disposal Method:** The generation of waste should be minimised or avoided wherever possible. Reuse or recycle products wherever possible. This material and its container must be disposed of in a safe way. Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners may retain some product residues and hence be potentially hazardous

**Precautions and methods to avoid:** Do not empty into drains. Dispose of surplus products and those that cannot be recycled via a licensed waste disposal contractor. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labelled with their contents.

**Section 14 Transport Information**

**This product is classified as a Dangerous Good for transport in Australia; ADG 7**  
**This product is classified as a Dangerous Good for transport: NZS 5433:2020 and SNZ HB 5433:2021**



## **Road, Rail, Sea and Air Transport**

<b>UN No</b>	1950
<b>Class - Primary</b>	2.1
<b>Subsidiary Risk</b>	6.1
<b>Proper Shipping Name</b>	AEROSOLS, FLAMMABLE, CONTAINING SUBSTANCES IN DIVISION 6.1, PACKING GROUP III
<b>Marine Pollutant</b>	NO
<b>Special Provisions</b>	63, 190, 277, 344, 327 Limited Quantities: 120ml

## **Section 15 Regulatory Information**

### **Australia:**

Classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia

Poison Schedule No: Not scheduled

### **New Zealand:**

This substance is hazardous according to the EPA Hazardous Substances (Classification) Notice 2020

EPA Approval Code: Aerosols (Flammable, Carcinogenic) - HSR002517

### **Controls in New Zealand:**

Trigger quantities for this substance:

<b>HSW (HS) Regulations 2017 and EPA Notices</b>	<b>Trigger Quantity</b>
Certified Handler	Not required
Location Certificate	3000L(AWC)
Tracking Trigger Quantities	Not required
Signage Trigger Quantities	3000L(AWC)
Emergency Response Plan	3000L(AWC)
Secondary Containment	3000L(AWC)
Fire Extinguishers	3000L(AWC) = 1
Restriction of Use	Only use for the intended purpose.

## **Section 16 Other Information**

### **Glossary**

EC <sub>50</sub>	Median effective concentration.
EEL	Environmental Exposure Limit.
EPA	Environmental Protection Authority
HSNO	Hazardous Substances and New Organisms.
HSW	Health and Safety at Work.
LC <sub>50</sub>	Lethal concentration that will kill 50% of the test organisms inhaling or ingesting it.
LD <sub>50</sub>	Lethal dose to kill 50% of test animals/organisms.
LEL	Lower explosive level.
OSHA	American Occupational Safety and Health Administration.
TEL	Tolerable Exposure Limit.

Product Name: Sabre Grip S20 500ml Aerosol  
Date of SDS: 3 May 2023

SDS Prepared by: Technical Compliance Consultants (NZ) Ltd  
Tel: +64 9 475 5240 WWW.techcomp.co.nz

TLV	Threshold Limit Value-an exposure limit set by responsible authority.
UEL	Upper Explosive Level
WES	Workplace Exposure Limit

References:

Australia:

1. Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice.
2. Standard for the Uniform Scheduling of Medicines and Poisons.
3. Australian Code for the Transport of Dangerous Goods by Road & Rail.
4. Model Work Health and Safety Regulations, Schedule 10: Prohibited carcinogens, restricted carcinogens and restricted hazardous chemicals.
5. Workplace exposure standards for airborne contaminants, Safe work Australia.
6. American Conference of Industrial Hygienists (ACGIH).
7. Globally Harmonised System of classification and labelling of chemicals.

New Zealand:

1. EPA Hazardous Substances (Safety Data Sheets) Notice 2017
2. Workplace Exposure Standards and Biological Exposure Indices APRIL 2022 edition.
3. Assigning a hazardous substance to a HSNO Approval (Aug 2013).
4. Transport of Dangerous goods on land NZS 5433:2020
5. HSW (Hazardous Substances) Regulations 2017

Disclaimer

This document has been prepared by TCC (NZ) Ltd and serves as the suppliers Safety Data Sheet ('SDS'). It is based on information concerning the product which has been provided to TCC (NZ) Ltd or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer. While TCC (NZ) have taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, TCC (NZ) Ltd accept no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS

The information herein is given in good faith, but no warranty, express or implied is made.

Please contact the Australian Manufacturer or New Zealand distributor, if further information is required.

Issue Date: 3 May 2023                      Review Date: 3 May 2028